STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765) Instructions for completing this report are



WELL ID # L33859

(START CARD) # 108543

Instructions fo	r complet	ting this rep	ort are on th	le last p	age of	this form			`		, <u>1</u>		
(1) OWNER: Well Number:								(9) LOCATION OF W					
								County KLAMATH Latitude Longitude					
Address 23333 N. POE VALLEY RD.										7E		·W.ofW	
City KLAMATH FALLS State OR Zip 97603								Section 7DA Tax lot 2800 Lot	NE t Block	1/4	SE Subdivi	1	/4
(2) TYPE OF	WOR	(:				- "		Street Address of Well		5734 E			
X New Well	_	_	Iteration (rep	air/reco	ndition)	Abandonr	nent	CHILOQUIN, OR					
(3) DRILL M	ETHOD):	•.					(10) STATIC WATER			-		
X Rotary Air		otary Mud	Cable			Auger	175 FT. ft. below land surface. Date 11/8/99 Artesian pressure NONE Ib. per square inch. Date						
(4) PROPOS		<u> </u>						(11) WATER BEARI					
X Domestic		community	Indust	rial		Irrigation		Depth at which water wa	as first found 181 F	Τ			
Thermal Injection Livestock Other							,				ated Flow	SWL	
(5) BORE H	OLE CO	NSTRUC	TION:							2 GPM	175		
Special Construction approval Yes XNo Depth of Completed Well 494 ft.											D GPM 5 GPM		<u>175</u> 175
Explosives used					Amou		·				y çı m		1/5
HOLE	.		SEAL	-	-	Amount		(12) WELL LOG:					
Diameter From 10				From 0	To	sacks or poun	nas	(,	Ground ele	evation 4	150		
6 5	0 494	BENTON	NITE		50	16 3/4 SAC	KS	N	Aaterial		From	То	SWL
								TOP SOIL			0	2	
		-						CEMENTED BROW	N CLAY & FINE (GRAVE		15	
	-						·····	YELLOW CLAY BROWN SANDSTO			<u>15</u> 22	<u>22</u> 43	
How was seal pl	aced: Me	ethod 🗌 A	ВХ	c 🗌	D]E		CEMENTED BROW			43	40	
Other								GRAVEL				90	
Backfill placed fi Gravel placed fi		ft. to ft. to		Naterial Size of gr				BROWN CLAY			90	108	
				HZE UI UI	avei _			CEMENTED BROW	N CLAY, SAND 8	FINE	108	181	
(6) CASING/	LINER:							GRAY CLAY W/STR	EAKS OF BLAC	K SAN	D 181	101	
Diame	12 1 11		Gauge Ste		astic	Welded Three	aded	& FINE GRAVEL				190	175
Casing:	6 +	1 249	.250				1	BLACK SAND & FIN	E GRAVEL		190	242	175
								GRAY CLAY			242	286	
				Ĵ				GRAY CLAY W/STR & FINE GRAVEL	EARS OF BLAC	n Jan	D 286	450	175
Liner:]				BLACK SANDSTON	IE, SAND, FINE		450		
Final location of]	GRAVEL & STREA	KS OF GRAY CL	AY		494	175
Final location of								REC	EIVED				
(7) PERFOR	ATIONS												
Perforati	ons	Method <u>N</u> Type	ONE	Mat	erial			NOV 1	6 1999				
From To	· Slot size	Number	Diameter	Tele/pi size		Casing Line	er		OURCES DEFT.				
							-		OREGON				
								Date started 11/2/99		pleted 11			
							-						
								(unbonded) Water Well I certify that the work I per				ahandor	ment
	·						, 	of this well is in compliance					
(8) WELL TE				ie is 1	noui			Materials used and information	tion reported above are	e true to n	ny best ki	nowledge	and
Pump		Bailer	XAir		L	Flowing Artesi	an	belief.		1474	(C Numb		
Yield gal/min	Dra	wdown	Drill ste	m at		Time		Signed J. But	Pinhard		/C Numb • <u>11/12</u>)
20 GPM			225 F1	Γ.		1 hr.							
						· · · · · · · · · · · · · · · · · · ·		(bonded) Water Well C					
	+							I accept responsibility for i					
Temperature of V	Water 50		Pepth Artesia	n Flow f	ound	NONE		performed on this well durin performed during this time i					ιĸ
Was a water ana			By whom					construction standards. Thi	-	-	••		elief.
Did any strata co						Foo little				14/14	/C Numb	er 777	
Saity Mu			olored X	Other]	00	SANDY		Signed Stephen	R Hugher	Date	• 11/12	/99	
Depth of strata:									<u> </u>				
ORIGINAL & F	IRST CO	OPY - WATI	ER RESOL	IRCES	DEPA	RTMENT	SECO	ND COPY - CONSTRUC	TOR THIRD C	OPY - C	USTON	IER	

ŝ,

-