

WASHINGTON
COUNTY SURVEYOR
RECEIVED 6/4/85
ACCEPTED
FOR FILING 6-6-85
HILLSBORO, OR

SURVEY FOR:
STIMSON LBR. CO.
IN

SECTIONS 13 & 14 T.3N. R.5W. W.M.
WASHINGTON COUNTY, OREGON
MAY 30, 1985 SCALE 1" = 400'

14-3N5-12
13-3N5-12
21,259
B

SURVEY PURPOSE
TO ESTABLISH CORNERS AND MARK RECORD TITLE
BOUNDARIES AS SHOWN

NARRATIVE

SECTION SUBDIVIDED ACCORDING TO "THE
MANUAL OF SURVEYING INSTRUCTIONS 1973"
BEARINGS BASED ON SURVEY 10368 BETWEEN
THE S.E. AND N.W. CORNERS OF SEC. 14. BEARINGS
ARE 0°07'12" LEFT OF HIGHWAY 26 BEARINGS.
I DIDN'T USE THE CORNER POSITION FOUND BY WILKES
IN SURVEY 2670 FOR THE 1/4 CORNER TO SECS. 12 & 13
BECAUSE WHAT HE FOUND HAD NO RELATION TO THE
ORIGINAL 1879 SURVEY. I DISCUSSED THIS WITH R.C.
PEARSON, WASHINGTON COUNTY SURVEYOR AND HE AGREED
WITH THIS CONCLUSION. I USED THE CORNER SET BY
SURVEY 19252.
BEARING TREES SCRIBED ACCORDING TO "MANUAL" EXCEPT AS NOTED.
BEARING TO BT'S TAKEN WITH MAGNETIC COMPASS DEC'L. 22°E.
DISTANCES MEASURED TO BT CENTERS.
YELLOW BEARING TREE TAGS NAILED TO ALL NEW BT'S

SURVEYED BY

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Richard A. Morris
OREGON
MAY 10, 1957
RICHARD A. MORRIS
401

RT.2 BOX 652
HILLSBORO, OR. 97123
PH. 628-2353

LEGEND

- = FOUND MONUMENTS AS NOTED
- = 1" IR P.C. SET 5/8" IRON ROD WITH YELLOW PLASTIC
CAP MARKED "MORRIS PLS 401"
- BT = BEARING TREE
- OSBF P.C. = OREGON STATE BOARD OF FORESTRY IRON PIPE WITH BRASS CAP
- 1 () = ORIGINAL SURVEY RECORD
- 2 () = WILKES SURVEY 3022 RECORD
- 3 () = WILKES SURVEY 2670 RECORD
- 4 () = MORRIS SURVEY 1964 RECORD
- 5 () = BASS SURVEY 10674 RECORD
- = TRUE LINE MARKED WITH ORANGE PLASTIC RIBBON
ALUMINUM TAGS AND TREE BLAZES

