NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

4.15			345/7E-15
State	Well	No.	345/76-15

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion. (Please type or print)

(Do not write above this line)

State	Well No.	345/16-1	<u></u>
State	Permit 1	No	

(1) OWNER: OCT 2 7 1975	(10) LOCATION OF WELL:			
NameJohn Kronenbuger	County Klamath Driller's well number			
NameJohn Kronenbuger Address P.O. Rox SMAJER RESOURCES DEPT. Chiloguin Oregon SMEM, OREGON	NW 14 NW 14 Section 15 T. 34	R. 7E		W.M.
	Bearing and distance from section or subdivisi	on corner		
(2) TYPE OF WORK (check):			-	<u></u>
New Well 🖺 Deepening 🗌 Reconditioning 🗎 Abandon 🗀				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 70			ft.
Rotary Driven Domestic X Industrial Municipal Domestic X	Static level 9 ft. below land s	urface. Da	ate 8-1	L5
Cable	Artesian pressure NONE lbs. per squar	e inch. Da	ate	
CASING INSTALLED: Threaded □ Welded ♥	(19) WELL LOC.			11
6	(12) WELL LOG: Diameter of well below casing6"			
	Depth drilled 92 ft. Depth of completed well 92 ft.			
	Formation: Describe color, texture, grain size and show thickness and nature of each stratum			
	with at least one entry for each change of forma	tion. Report	t each ch	hange in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	cipal water	-bearing) strata.
Type of perforator used	MATERIAL	From	То	swL
Size of perforations in. by in.	Sandy soil	0	5	
perforations from ft. to ft.	Brown Clay and Gravel Mix	5	12	
perforations from ft. to ft.	Blue Clay	12	57	
perforations from ft. to ft.	Clay and Sand Mix	57	65	
(A) COMMINIO	Sandy Clay	65	70	
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	Layers of Hard Clay and Sand	70	92	91
Manufacturer's Name				
Type Model No.		\vdash		
Diam. Slot size		ļ		
Diam. Slot size Set from ft. to ft.		 		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	· · · · · · · · · · · · · · · · · · ·			
Was a pump test made? Yes No If yes, by whom?				
Yield: gal./min. with ft. drawdown after hrs.				
,, , , , , , , , , , , , , , , , , , , ,		 		
n " "	·			
Bailer test 30 gal./min. with ft. drawdown after 2 hrs.				
Artesian flow g.p.m.				
perature of water 45 Depth artesian flow encountered ft.	Work started 8-14 1975 Complet	ed 8-1 5	 5	175
(9) CONSTRUCTION:	Date well drilling machine moved off of well	8-15		₁₉ 75
	Drilling Machine Operator's Certification:			
Well seal—Material usedcement and benonite	This well was constructed under my			
Well sealed from land surface to	Materials used and information reported best knowledge and belief	above ar	e true	to my
Diameter of well bore below seal		Data 10	2.6	10.75
Number of sacks of cement used in well sealsacks	[Signed] / Out (Drilling Machine Operator)	Date .10	- 	, 118/
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.	196		
Brand name of bentoniteAqua -Ge1				
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:			
of waterlbs./100 gals.	This well was drilled under my jurisd true to the best of my knowledge and bel		this re	port is:
Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.	1			
Did any strata contain unusable water? Yes X No	NameNorm Sevey Wellbrilling (Person, firm or corporation)			
Type of water? depth of strata	Address 5619 Leland Drive	97601		
Method of sealing strata off	[Signed] Horn Sever			-
Was well gravel packed? Yes No Size of gravel:	(Water Well Contr	ractor)		
Gravel placed fromft. toft.	Contractor's License No. 408 Date	0-24		, 19. <u>75</u>