Attention Owner:

Confidentiality Privilege Notice on reverse side of owner's copy.

Texas Department of License and Regulation Water Well Driller/Pump Installer Program

Water Well Driller/Pump Installer Program
P.O. Box 12157 Austin, Texas 78711 (512)463-7880 FAX (512)463-8616
Toll free (800)803-9202

Email address: water.well@license.state.tx.us

This form must be completed and filed with the department and owner within 60 days upon completion of the well.

WELL REPORT

A. WELL IDENTIFICATION AND LOCATION DATA 1) OWNER										
NameWay Back Layed Back				City			State	Zip	Zip	
Ranch-Jim Toungate	7303 Foster Island			Richmond			TX 77469		469	
Ranch-Jim Toungate 7303 Foster Island Richmond TX 77469 2) WELL LOCATION										
County Physical Address High Crossing City							State	Zip		
Bastrop Rd. S.E. of Rosanky				Rosanky			TX	78	953	
3) Type of Work Lat. 29 55 52 Lon							Grid#			
New Well Reconditioning								5)	N↑	
Replacement Deepening										
	Rig Supply If Public Supply w									
6) Drilling Date	Diameter of Hole			7) Drilling Method (check) Upriven				@		
Started 5 / 03 / 04	Dia.(in) From (ft) To (ft)			Air Rotary Mud Rotary Dored						
*,	9 7/8 0 816			Air Hammer Cable Tool I Jetted						
Completed 5 / 07 . / 04		200	* _F	Othe	r					
							10			
From (ft) To (ft) Description and color of formation material 8) Borehole Completion Open Hole Straight								ht Wall		
				☐ Under-reamed ※ Gravel Packed ☐ Other						
				If Gravel Packed give the interval from 758 ft. to 816 ft. Casing, Blank Pipe, and Well Screen Data						
4 9 Red clay				Casii	New New	Steel, Plastic		1	Gage	
	llow clay/iron rock			Dia.	Or	Perf., Slotte	d. etc	Setting (ft)	Casing	
46 60 Sandy gray shale/iron rock				(in.)	Used		. if commercial			
60 95 Black-gray sand/iron rock				5.	N	SDR17 P		+2 774		
95 170 Swampy green-gray shale				5	N	SDR17 M		774 81		
170 198 Sandy brown shale/sand					N	SDR17 P	oint	814 81	6	
198 230 Gray shale/small rocks/lignite										
230 267 Sandy gray shale/lignite/sand					9) Cementing Data Cementing from					
267 304 Fine to medium gray sand/rocks										
(Use reverse side of Well Owner's copy. If necessary) Continued										
13) Plugged Well plugged within 48 hours										
Casing left in well: Cement/Bentonite From (ft) To (ft) From (Method of verification of above distance						
Tom (t) Tom	10(11)	Sacks u	scu	10) 6	rface Co	munlation				
				10) Surface Completion X Specified Surface Slab Installed						
		☐ Specified Surface Sleeve Installed								
14) Type Pump ☐ Turbine ☐ Jet ☐ Submersible ☐ Cylinder				☐ Pitless Adapter Used☐ Approved Alternative Procedure Used☐						
Other										
Depth to pump bowls, cylinder, jet etc., 200 ft, 15) Water Test				11) Water Level						
Typetest Pump Bailer X Jetted Estimated				Static level 116 ft. below Date 5 / 07 / 04 Artesian Flow gpm. Date / /						
Yield: 100 gpm with 0 ft. drawdown after hrs. 16) Water Quality				12) Packers Type Depth						
Did you knowingly penetrate a strata which contain undesirable constituents.										
YES NO If yes, did you submit a REPORT OF UNDESIRABLE WATER Type of water Depth of Strata				N/A						
Was a chemical analysis made ☐ Yes 又 No						11/1				
Company or individual's Name (type or print)							Lic. No. 144	46WPKL		
Richter Well Drill				ing. Inc.			Dic. 140. WWI	WWDAPP538		
Address P.O. Box 188 City				Flatonia S			State TX Zip 78941			
Signature	ter 51	11 / 04	Sign	nature (Janie	Kalie		5 / 13	-	
Licensed Driller/Pump Install	er - Land	Date	(A) 100		App	rentice	1000	Dat	30000000000000000000000000000000000000	