MONTANA WELL LOG REPORT

Other Options

This well log reports the activities of a licensed Montana well driller, serves as the official record of work done within the borehole and casing, and describes Plot this site on a topographic map the amount of water encountered. This report is compiled electronically from the contents of the Ground Water Information Center (GWIC) database for this site. Acquiring water rights is the well owner's responsibility and is NOT

Return to menu

accomplished by the filing of this report. Site Name: BREKKE, RAY & KARI

Section 7: Well Test Data

GWIC Id: 228799

Total Depth: 180 Static Water Level: 70 Water Temperature:

Section 1: Well 5925 LINCOLN RD.

Air Test *

HELENA MT 59602 [05/05/2006]

Section 2: Location

	rownsnip	Range	Section	Quarter	sectio	ons	15 gpm with drill stem set at 1
	11N	04W	6	NW1/4	NW¼		Time of recovery 0.18 hours.
		County		G	eoco		Recovery water level 70 feet.
	LEWIS AND CL	.ARK					Pumping water level feet.
	Latitude	Longi	tude	Geomethod	D	atum	r diriping water level _ leet.
	46.746345	112.16	6878	TRS-SEC	N	AD83	
Ground Surface Altitude			Method Datum Date		Date	* During the well test the disch	
							uniform as possible. This rate m
	Addition			Bloc	ck	Lot	sustainable vield of the well. Su

* During the well test the discharge rate shall be as uniform as possible. This rate may or may not be the sustainable yield of the well. Sustainable yield does not include the reservoir of the well casing.

15 gpm with drill stem set at 180 feet for 1 hours.

Section 3: Proposed Use of Water

DOMESTIC (1)

Section 8: Remarks

Section 4: Type of Work Drilling Method: ROTARY

MANLEY O MARTENSON

Section 9: Well Log **Geologic Source** Unassigned

70 CLAY

180 HARD CLAY

Section 5: Well Completion Date

Date well completed: Friday, May 05, 2006

Section 6: Well Construction Details

From To Description

0

Borehole dimensions							
From	То	Diameter					
0	180	6					

Borehole dimensio				
From	То	Diameter		
0	180	6		
Casin	a			

Casin	g								
			Wall	Pressure					
From	То	Diameter	Thickness	Rating	Joint	Туре			
2	18	6	0.250		WELDED	A53B STEEL			
						PVC-SDR			
10	180 4	4		200.00	WELDED	200			
Comp	letio	on (Perf/S	creen)						
			# of	Size of					
From	То	Diameter	Openings	Openings	Descript	tion			
80	120	4		.020	FACTOR	RY SLOTTED	Driller	Cert	tification

Annular Space (Seal/Grout/Packer)

Cont. From To Description Fed? 18 BENTONITE Y

160 180 4

FACTORY SLOTTED All work performed and reported in this well log is in compliance with the Montana well construction standards.

This report is true to the best of my knowledge.

Company: H & L DRILLING INC License No:WWC-447

Date 5/5/2006 Completed: