

Klam
657

AUG 10 1982

State Well No. 318/7E-17

WATER RESOURCES DEPT.
SALEM, OREGON

State Permit No.

(10) LOCATION OF WELL:

County	Klamath			Driller's well number		
NE ¼ NE ¼ Section	17	T. 31	S. R. 7 E	W.M.		
Tax Lot #	Lot 28	Blk 28	Subdivision			
Address at well location:	Off of highway 232, by Scott Creek					

(11) WATER LEVEL: Completed well.

Depth at which water was first found	100	ft.
Static level	82	ft. below land surface. Date 7-27-82
Artesian pressure		lbs. per square inch. Date

(4) PROPOSED USE (check):

Rotary Air	☐	Driven	☐	Domestic	☒	Industrial	☐	Municipal	☐
Rotary Mud	☐	Dug	☐	Irrigation	☐	Test Well	☐	Other	☐
Compressed Air	☒	Bored	☐	Thermal:		Withdrawal	☐	Reinjection	☐

Steel	☒	Plastic	☐
Threaded	☐	Welded	☒

6" Diam. from +1 ft. to 99 ft. Gauge .250

LINER INSTALLED:

....." Diam. from ft. to ft. Gauge

(6) PERFORATIONS:

Perforated? ☐ Yes ☒ No

Type of perforator used		
Size of perforations	in. by	in.
..... perforations from	ft. to	ft.
..... perforations from	ft. to	ft.
..... perforations from	ft. to	ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name

Type Model No.

Diam. Slot Size Set from ft. to ft.

Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?			
Flow:	gal./min. with	ft. drawdown after	hrs.
"	"	"	"
Air test	15 gal./min. with drill stem at	110 ft.	1 hrs.
Bailer test	gal./min. with	ft. drawdown after	hrs.
Artesian flow	g.p.m.		
Temperature of water	48	Depth artesian flow encountered ft.	

(9) CONSTRUCTION:

Special standards: Yes ☐ No ☒

Well seal—Material used Cement & 5% Bentonite
Well sealed from land surface to 25 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 8 sacks
How was cement grout placed? Pumped

Was pump installed? NO Type HP Depth ft.
 Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
 Did any strata contain unusable water? ☐ Yes ☒ No
 Type of Water? depth of strata
 Method of sealing strata off
 Was well gravel packed? ☐ Yes ☒ No Size of gravel:
 Gravel placed from ft. to ft.

(12) WELL LOG:

Diameter of well below casing 6"

Depth drilled **110** ft. Depth of completed well **102** ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

[illegible]

Work started	7-26	19 82	Completed	7-27	19 82
Date well drilling machine moved off of well				7-27	19 82

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] John L. Murphy Date 7-31, 1982
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1388

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Norm Sevey Well Drilling, Inc.
(Person, firm or corporation)

Address 800 Old Midland Rd. Klamath Falls, OR

[Signed] Naim Sevey
(Water Well Contractor)

Contractor's License No. 408 Date 7-31 19 81

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

SP*12658-690