STATE OF OREGON Water Supply Well Report

instructions for completing this report are on the last page of this form.

(as required by ORS 537.765)

' YAMH 53558

YAMH53558

Received Date:

Well ID Tag # L

Start Card #

61335 113744

(1) Owner Well Number:	(9) Location of Hole by legal description
Name: TIM MASON	County: YAMH Latitude: Longitude:
Street: 0.4665 NE BUILDING	Township: 3.00 S Range: 3.00 W
Street: 24385 NE DILLON DR. City: NEWBERG State:OR Zip Code: 97132	Section: 14 NWNW Lot: Block:
(2) Type of Work	Tax Lot: 700 Subdivision:
X New Alter (Recondition) After (Repair)	Street Address of Well (or nearest address): NEXT DOOR TO 20260 HWY, 240
Deepening Abandonment	MAP, with location identified, must be attached.
(3) Drill Method	
	(10) Static Water Level Feet below land surface: 64.0 Date: 10 / 17 / 2003
X Rotary Air Rotary Mud Cable Auger Other:	Feet below land surface: 64.0 Date: 10 / 17 / 2003 Artesian Pressure: Date:
(4) Proposed Use	(11) Water Bearing Zones
X Domestic Community Industrial Irrigation Injection	Depth at which water was first found: 158.00 ft. From To est Flow swl
LivestockThermal Other:	From To est Flow swl 158.00 173.00 30.00 64
(5) Bore Hole Construction	•
Special Standards: Depth of completed well: 158.00 ft.	
Explosives Used: Amount: Type:	(12) Well Log Ground Elevation:
Hole Seal	Material From To swl
Diameter From To Mtrl From To Sacks/lbs	TOP SOIL 0.00 2.00
10.00 0.00 50.00 GB 0.00 50.00 23	CLAY BROWN 2.00 21.00
6.00 50.00 200	GARY BROWN SANDSTONE 21.00 70.00 64
	CLAYSTONE SOFT 70.00 158.00 SANDYCLAYSTONE SOFT 158.00 173.00
How was seal placed? Other: BENTONITE	SANDYCLAYSTONE SOFT
Back fill placed from: Material:	CAVE BACK TO 158 158,00 200,00
Filter pack from: Size:	
(6) Casing / Liner	
Csng/ Shoe Shoe	
Liner Diameter From To Gauge Mtrl Weld Thrd at used C 6.00 -1.00 57.00 250 S X 57	
L 4.00 100.00 200.00 160 P	
	neceiven
	RECEIVED
(7) Perforation / Screens	250
Perforations: Csng/	DEC 0 1 2003
Mtrl From To Width Height #Slots Dia. t/pSize Lnr Method	WATER RESOURCES DEPT
P 100.00 200.00 32.00 60 4.00 L SAW Screens:	SALEM, OREGON
Mtrl From To S Size #Slots Dia. t/pSize Type Gauge	
(8) Well Tests (Minimum testing time is one hour)	
Type Yield Units Drawdown Stem at Duration	Date Started: 10 / 13 / 2003 Date Completed: 10 / 18 / 2003
A 30.00 G 150.00 1.00	(unbonded) Water Well Constructor Certification:
	I certify that the work I perform on the construction, alteration, or abandonment
	of this well is in compliance with Oregon well construction standards. Materials used and information reported above are true to the best knowledge and belief.
Temperature of Water: 54 F	Signed by: WWC #:
Was water analysis done? Depth of artesian flow:	(bonded) Water Well Constructor Certification:
by whom?	I accept responsibilty for the construction, alteration, or abandonment work performed on this well during the construction dates reported above. All work
Did any strata contain water unsuitable for use? Too Little Salty	performed during this time is in compliance with Oregon well construction
Muddy Colored other:	standards. This report is true to the best of my knowledge and belief. Signed by: GLENN A ANTHONY WWC #: 1229
Depth of strata:	ANTHONY MELL DOLLING & DUMPO INCO.