

Send original copy by certified mail to the Texas Department of Water Resources P. O. Box 13087 Austin, Texas 78711

State of Texas
WATER WELL REPORT

For TDWR use only
Well No. 41-40-9F
Located on map Y83
Received: C.F.S.

ATTENTION OWNER: Confidentiality Privilege Notice on Reverse Side

1) OWNER Jimmie Lewis (Name) Address P.O. Box 171 (Street or RFD) Hatesville, TX (City) (State) (Zip)
2) LOCATION OF WELL: County Coryell 1/2 miles in West (N.E., S.W., etc.) direction from Peak (Town)

Driller must complete the legal description to the right with distance and direction from two intersecting section or survey lines, or he must locate and identify the well on an official Quarter- or Half-Scale Texas County General Highway Map and attach the map to this form.

Legal description:
Section No. _____ Block No. _____ Township _____
Abstract No. _____ Survey Name _____
Distance and direction from two intersecting section or survey lines _____

See attached map. map on 41-40-9F

3) TYPE OF WORK (Check):
 New Well Deepening Reconditioning Plugging
4) PROPOSED USE (Check):
 Domestic Industrial Public Supply Irrigation Test Well Other _____
5) DRILLING METHOD (Check):
 Mud Rotary Air Hammer Driven Bored Air Rotary Cable Tool Jetted Other _____

6) WELL LOG:

Date drilled	DIAMETER OF HOLE		
	Dia. (in.)	From (ft.)	To (ft.)
<u>8-3-81</u>	<u>8</u>	<u>Surface</u>	<u>130</u>
	<u>6 1/4</u>	<u>13</u>	

7) BOREHOLE COMPLETION:
 Open Hole Straight Wall Underreamed
 Gravel Packed Other _____
If Gravel Packed give interval . . . from _____ ft. to _____ ft.

From (ft.)	To (ft.)	Description and color of formation material
<u>0</u>	<u>20</u>	<u>yellow clay</u>
<u>30</u>	<u>95</u>	<u>gray shale</u>
<u>95</u>	<u>100</u>	<u>dark gray sand</u>
<u>100</u>	<u>429</u>	<u>gray shale</u>
<u>429</u>	<u>439</u>	<u>white rock</u>
<u>439</u>	<u>440</u>	<u>red</u>
<u>440</u>	<u>460</u>	<u>white rock w/red clay</u>
<u>460</u>	<u>480</u>	<u>soft gray red & red clay</u>
<u>480</u>	<u>495</u>	<u>soft pink rock & clay</u>
<u>495</u>	<u>500</u>	<u>water</u>
<u>500</u>	<u>530</u>	<u>red rock & clay</u>
<u>530</u>	<u>534</u>	<u>conglomerate rock</u>

8) CASING, BLANK PIPE, AND WELL SCREEN DATA:

Dia. (in.)	New or Used	Steel, Plastic, etc. Perf., Slotted, etc. Screen Mgf., if commercial	Setting (ft.)		Gage Casing Screen
			From	To	
<u>6 5/8</u>	<u>New</u>	<u>Steel</u>	<u>surf.</u>	<u>130</u>	<u>180</u>
<u>5 1/2</u>	<u>New</u>	<u>Steel</u>	<u>366 to 534</u>		<u>188</u>
<u>5 1/4</u>	<u>New</u>	<u>Styrene</u>	<u>126 to 366</u>		

CEMENTING DATA
Cemented from surface ft. to 130 ft.
Method used Grout
Cemented by Armed Drilling & Supply Co. (Company or Individual)

9) WATER LEVEL:
Static level 275 ft. below land surface Date 8-4-81
Artesian flow _____ gpm. Date _____

10) PACKERS: Type _____ Depth _____

RECEIVED

SEP 17 1982

DEPT. OF
WATER RESOURCES

(Use reverse side if necessary)

11) TYPE PUMP:
 Turbine Jet Submersible Cylinder
 Other _____
Depth to pump bowls, cylinder, jet, etc., 360 ft.

13) WATER QUALITY: