

SITUATED IN

The State of Ohio, County of Noble,
Township of Jackson, and being a part
of the SW Qtr. of Sec. 29 & SE Qtr. of
Sec. 30, T5, R9.

BASIS OF BEARING

Bearings and distances are based on State Plane Grid Coordinates,
NAD83, Ohio South, per GPS Observation.

REFERENCES

* As Noted on Plat



Brian Kelly McPeck
Reg. Surveyor No. 8517

DAVID J. & DIANE M. HESS
OR 101-743

Parcel # See description
Acreage Conveyed _____
Acreage Remaining _____
Noble County Engineer K9

LINE TABLE


LINE	BEARING	DISTANCE
L1	N 00°49'34" W	253.44'
L2	S 17°08'48" E	104.61'
L3	S 17°22'32" E	150.14'
L4	S 21°36'53" E	53.63'
L5	S 26°59'45" E	37.30'
L6	S 37°43'11" E	50.74'
L7	S 36°45'27" E	95.88'
L8	S 27°03'40" E	32.39'
L9	S 14°48'48" E	78.49'
L10	S 17°00'23" E	123.29'
L11	S 28°20'03" E	36.34'
L12	S 29°52'34" E	33.99'
L13	S 22°14'56" E	29.81'
L14	S 09°20'41" E	25.10'
L15	S 00°36'34" W	74.11'
L16	S 36°04'27" W	26.79'
L17	S 25°49'16" W	34.83'
L18	S 19°45'22" W	17.25'

DESCRIPTION APPROVED

LEGEND

- ▲ Railroad Spike Found
- △ Railroad Spike Set
- Iron Pin Found
- Pipe Found w/cap
- ⊠ Stone Found
- Z- Property Hook
- ⊙ Iron Pin Set
- ⊗ Axle Found

Graphic Scale



(IN FEET)
1 inch = 400 ft.



www.mcpeeklandsurveying.com
email: brian@mcpeeklandsurveying.com
340 Robin Hood Ln., * Zanesville, Oh 43701 * 740.704.6073