LEGAL DESCRIPTION (LAND IN NW1/4 OF NW1/4) The Northwest 1/4 of the Northwest 1/4 of Section 21, Town 11 North, Range 10 East, except land platted as Birch Crest PLAT OF SURVEY LEGAL DESCRIPTION (LAND IN NW1/4 OF SW1/4 AND LAND IN SW1/4 OF NW1/4) Acres, Dayton Township, Tuscola County, State of Michigan more particularly described as: Commencing at the Northwest The Northwest 1/4 of the Southwest 1/4 and the Southwest 1/4 of the Northwest 1/4 of Section 21, Town 11 North, Range 10 East, Dayton Township, Tuscola County, State of Michigan Corner of said Section 21 which is marked with a 1 1/2 inch pipe; thence S.01°06'55"E., 227.28 feet along the West Line of said is described as: Commencing at the West 1/4 Corner of said Section 21 which is marked with a "T" iron; thence N.01°06'55"W., 1317.58 feet to the Northwest Corner of the Southwest Section 21 to the Southwest Corner of Lot 1 of the plat of Birch Crest Acres as recorded in Liber 3, Page 12, Tuscola County 1/4 of the Northwest 1/4 of said Section 21, said point is marked with a 1/2" diameter re-rod; thence along the North line of the Southwest 1/4 of the Northwest 1/4 of said Section 21, records and the Point of Beginning; thence bounded by the water's edge of Phelps Lake as referenced by a traverse line PART OF SECTION 21, N.88°29'09"E., 1327.19 feet to the Northeast Corner of the Southwest 1/4 of the Northwest 1/4 of said Section 21, said point falls in Phelps Lake and is referenced by a 4 foot long iron extending across lots 1 to 25 in the plat of Birch Crest Acres, the following 9 courses; (1) thence N.76°58'09"E., 123.16 feet; (2) rod with a 2" aluminum disk cap stamped R.A. Duthler Land Surveyor, Imlay City, Michigan that is S.88°29'09"W., 627.00 feet from said point, it is also referenced by a 4 foot long rod thence S.87°46'11"E., 146.90 feet; (3) thence S.47°53'51"E., 118.70 feet to a found concrete monument; (4) thence TOWN 11 NORTH, RANGE 10 EAST, inside a 2 inch diameter pipe that is 5 feet long and has a cap stamped A & B RR Land Line, R.A. Duthler Land Surveyor that is S.01°09'47"E., 230.00 feet from said point; thence along the S.37°08'03"E., 190.41 feet (190.58 feet record); (5) thence S.51°45'30"E., 211.65 feet; (6) thence S.22°24'51"E., 247.81 feet East line of the Southwest 1/4 of the Northwest 1/4 of said Section 21, S.01°09'47"E., 1319.89 feet to a point on the East-West 1/4 line of said Section 21, said point is marked with a 1/2" SURVEYOR'S CERTIFICATE DAYTON TOWNSHIP, TUSCOLA COUNTY, ع∠∠ ر (248.00 feet record) to a found concrete monument; (7) thence S.45°21'21"E., 155.00 feet; (8) thence S.68°21'21"E., 200.00 diameter re-rod; thence along the East line of the Northwest 1/4 of the Southwest 1/4 of said Section 21, S.01°18'29"E., 1329.25 feet to the Southeast Corner of the Northwest 1/4 of feet; (9) thence S.46°21'21"E., 332.73 feet (332.00 feet record); thence leaving said traverse line, N.88°50'13"E., 78.97 feet I hereby certify that I have surveyed and mapped STATE OF MICHIGAN. the Southwest 1/4 of said Section 21, said point is marked with a 1/2" re-rod approximately 6 feet south of a 40 inch diameter beech tree; thence along the South line of the Northwest (83.00 feet record) to a point on the East Line of the Northwest 1/4 of the Northwest 1/4 of said Section 21, said point is the land above platted and/or described on Jan. 1/4 of the Southwest 1/4 of said Section 21, S.88°28'56"W., 1326.03 feet to a point on the West line of said Section 21, said point is referenced by a 1/2" diameter re-rod N.88°28'56"E., 19, 2011 and that the ratio of closure on the marked with a 4' long rod 4'± west of a found T-bar and broken concrete monument; thence along said East Line of the 40.00 feet from said point; thence along said West line, N.01°24'18"W., 1331.64 feet to the West 1/4 Corner of said Section 21 and the Point of Beginning and Containing 80.730 acres unadjusted field observations of such survey was ıR TAC TAG AG Northwest 1/4 of the Northwest 1/4, S. 01°09'47"E., 74.89 feet to the Southeast Corner of the Northwest 1/4 of the 1/219,567 or less and complies with P.A. 132 Northwest 1/4 of said Section 21, said point falls in Phelps Lake and is referenced by a 4 foot long iron rod with a 2" aluminum of 1970 as amended EXCEPT for section 3.(1) Subject to a 120 foot drain easement, 60 feet on each side of the centerline, for the Phelps Lake Drain as recorded in Liber 1097, pages 484 to 485. disk cap stamped R.A. Duthler Land Surveyor, Imlay City, Michigan that is S.88°29'09"W., 627.00 feet from said point, it is also Subject to a 120 foot drain easement, 60 feet on each side of the centerline, for the Phelps Lake Drain as recorded in Liber 1097, pages 490 to 491. referenced by a 4 foot long rod inside a 2 inch diameter pipe that is 5 feet long and has a cap stamped A & B RR Land Line, R.A. Subject to the rights of the public for highway purposes along Pattison Road. Duthler Land Surveyor that is S.01°09'47"E., 230.00 feet from said point; thence along the South Line of the Northwest 1/4 of Subject to all easements, restrictions, and rights of way of record. the Northwest 1/4 of said Section 21, S.88°29'09"W., 1327.19 feet to a point on the West Line of said Section 21; thence 37.85' NE TO TAG #47200 IN SE FC. TW. 11" CEDAR. N.01°06'55"W., 1090.30 feet along the West Line of Section 21 to the Point of Beginning and containing 19.394 acres including FOU 30. 61. 62. 36. 1.37' NNE TO TAG #47200 IN E FC. 25" PINE. RICHARD A. DUTHLER P.S. 16.51' S. TO TAG #47200 IN W. FC. 6" THORNAPPLE. No. 47200 26.30' NW TO 600" NAIL IN W. FC. 12" ELM. S. 1/4 COR Subject to a 120 foot drain easement, 60 feet on each side of the centerline, for the Phelps Lake Drain as recorded in Liber 65.35' WNW TO TAG IN S. FC. 30" MAPLE 48.68' SW TO TAG #47200 IN N. FC. 12" MAPLE SECTION 21 34.73' S. TO TAG #47200 IN W. FC. 12" ASH. 94.18' SE TO PK NAIL IN SW FC. OF A P.P. Subject to all easements, restrictions, and rights of way of record. N 01°12'39" W 2653.74' N-S 1/4 LINE OF SECTION 21 DID NOT FIND OBJECT AND DID NOT SET. N-S 1/4 LINE OF SECTION 21 N. 1/4 COR. SECTION 21 T.11N., R.10E. S 01°12'39" E 2644.38' **LEGAL DESCRIPTION (COMBINED LAND IN SECTION 21)** 1322.19 The Northwest 1/4 of the Southwest 1/4 and the West 1/2 of the Northwest 1/4 of Section 21, Town 11 North, Range 10 East, except land platted as Birch Crest Acres, Dayton Township, Tuscola County, State of Michigan more particularly described as: Beginning at the West 1/4 Corner of said Section 21 which is marked with a "T" iron; thence N.01°06'55"W., 2407.88 feet to the Southwest Corner of Lot 1 of the plat of Birch Crest Acres as recorded in Liber 3, Page 12, Tuscola County records; thence bounded by the water's edge of Phelps Lake as referenced by a traverse line extending across Lots 1 to 25 in the plat of Birch Crest Acres, the following 9 courses; (1) thence N.76°58'09"E., 123.16 feet; (2) thence -NO TITLE WORK HAS BEEN SUPPLIED BY THE CLIENT FOR PURPOSES OF THIS SURVEY. S.87°46'11"E., 146.90 feet; (3) thence S.47°53'51"E., 118.70 feet to a found concrete monument; (4) thence S.37°08'03"E., 190.41 feet (190.58 THEREFORE, NO GUARANTEE IS MADE THAT feet record); (5) thence S.51°45'30"E., 211.65 feet; (6) thence S.22°24'51"E., 247.81 feet (248.00 feet record) to a found concrete monument; (7) ANY OR ALL EASEMENTS, RECORDED OR thence S.45°21'21"E., 155.00 feet; (8) thence S.68°21'21"E., 200.00 feet; (9) thence S.46°21'21"E., 332.73 feet (332.00 feet record); thence leaving UNRECORDED, ARE SHOWN ON THIS said traverse line, N.88°50'13"E., 78.97 feet (83.00 feet record) to a point on the East Line of the West 1/2 of the Northwest 1/4 of said Section 21, -THIS SURVEY IS ROTATED TO TRUE NORTH. said point is marked with a 4' long rod 4'± west of a found T-bar and broken concrete monument; thence along said East Line of the West 1/2 of the Northwest 1/4, S. 01°09'47"E., 1394.78 feet to a point on the East-West 1/4 line of said Section 21, said point is marked with a 1/2" diameter -TREES SHOWN ON THIS SURVEY ARE FOR DRAFTING PURPOSES ONLY. ACTUAL NUMBER, SIZE, AND LOCATION HAVE NOT BEEN DETERMINED. re-rod; thence along the East line of the Northwest 1/4 of the Southwest 1/4 of said Section 21, S.01°18'29"E., 1329.25 feet to the Southeast Corner of the Northwest 1/4 of the Southwest 1/4 of said Section 21, said point is marked with a 1/2" re-rod approximately 6 feet south of a 40 inch diameter beech tree; thence along the South line of the Northwest 1/4 of the Southwest 1/4 of said Section 21, S.88°28'56"W., 1326.03 feet to a point on the West line of said Section 21, said point is referenced by a 1/2" diameter re-rod N.88°28'56"E., 40.00 feet from said point; thence SURVEY, BOTH ABOVE AND BELOW GROUND, ARE SHOWN FROM INFORMATION OF RECORD along said West line, N.01°24'18"W., 1331.64 feet to the West 1/4 Corner of said Section 21 and the Point of Beginning and Containing 100.124 SUPPLIED TO THE SURVEYOR AND A acres including that area covered by water. VISUAL INSPECTION OF THE PREMISES; NO Subject to a 120 foot drain easement, 60 feet on each side of the centerline, for the Phelps Lake Drain as recorded in Liber 1097, pages 484 to 485. GUARANTEE IS GIVEN AS TO THE COMPLETENESS AND ACCURACY THEREOF. Subject to a 120 foot drain easement, 60 feet on each side of the centerline, for the Phelps Lake Drain as recorded in Liber 1097, pages 490 to 491. EXACT LOCATION SHOULD BE VERIFIED IN THE Subject to a 120 foot drain easement, 60 feet on each side of the centerline, for the Phelps Lake Drain as recorded in Liber 1097, pages 502 to 506. FIELD WITH THE UTILITY COMPANY PRIOR TO Subject to the rights of the public for highway purposes along Pattison Road and Phelps Lake Road. ANY CONSTRUCTION WHICH MAY AFFECT THE Subject to all easements, restrictions, and rights of way of record. CONTRACTOR NOTE: The locations of existing underground utilities are shown in an approximate way only. The contractor shall determine the exact location of all existing utilities before commencing work. He agrees to be fully responsible for anv and all damages which might be occasioned by his failure to exactly locate and preserve any and all underground utilities. -3 WORKING DAYS **BEFORE YOU DIG** CALL MISS DIG These standard symbols wil OF FOUND CONCRETE MONUMENT GOVERNMENT CORNER MEASURED RECORDED SET A 1/2" X 4' LONG-REROD WITH A 2" ALUM. DISK STAMPED R.A. DUTHLER LAND SURVEYOR IMLAY CITY MI 5'± FROM THE WATERS EDGE. 100.124 ACRES SW CORNER SECTION 2 -NW CORNER SECTION 2

SUBJECT TO ALL EASEMENTS, RESTRICTIONS, AND RIGHT OF